

ANNEXURE 1

PROJECT: RATAN TATA GALLERY

LEGEND REF:

CST-3

Project No.:

Area: Display Wall

Date: 23rd March'24

Item: 3 Circuit H-Profile Suspended Track

Qty: (In Mtr.) 55

Model No.: EUTRAC H-Profile With 3 Circuit Track

Description: Aluminium-Extruded H-Profile, with provision for insertion and fixing of 3-Ckt track, complete with all rigid threaded stud suspension + coupling accessories.

Colour: Grey (Subject to approval)

Lamp: N/A

Beam Angle: N/A

Lamp Base: N/A

Total Wattage: N/A

Control Gear: N/A

Protection (IP): 20


Accessories

Dimensions: Width: 36mm; Height: 70mm; Length: As per site



Notes:

This is a generic specification based on a manufacturer's p
To be read in conjunction with contract drawings and docu
Vendor/Manufacturer to provide sample for approval by the
Installation method as per manufacturer's specs.



PROJECT: RATAN TATA GALLERY

LEGEND REF:

CST-2

Project No.:

Area: Display Shelf

Date: 23rd March'24

Item: Megnetic Track

2000mm Lenght Qty: (In Nos.)

5

Model No.: Generic

1000mm Lenght Qty: (In Nos.)

Description: Surface mounted 24V/48V megnetic micro track system. in black finish, with all connection, onboard dimmable power supply and fixing accessories as described



Colour: Black (Subject to approval)

Lamp: N/A

Beam Angle: N/A

Lamp Base: N/A

Total Wattage: N/A

Control Gear: N/A

Protection (IP): 20

Accessories:

Dimensions: As per image

Notes:

This is a generic specification based on a manufacturer's product

To be read in conjunction with contract drawings and documents

Vendor/Manufacturer to provide sample for approval by the consultant before installation

Installation method as per manufacturer's specs.

PROJECT: RATAN TATA GALLERY

LEGEND REF:

TSL-1B

Project No.:

Area: Display Shelf

Date: 23rd March'24

Item: Adjustable track mounted projectors

Qty: (In Nos.) 3

Model No.: Generic

Description: Adjustable 3-circuit track-mounted variable beam spotlight for LED lamp with built-in on board dimmable power supply. Additional accessories must be possible, viz, antiglare louver, and color filters.



Colour Grey (Subject to approval)


Lamp 30W LED 1800lm within SCDM 3, 90+ CRI, 3000° K

Beam Angle Variable Beam (6° to 36°)

Lamp Base N/A

Total Wattage 33W

Control Gear Integral dimmable LED driver (on board) with minimum 0.9PF, THDi≤10% & Current ripple ≤20%



Protection (IP) 20

Accessories honeycomb louver

Dimensions: As per image

Notes: This is a generic specification based on a manufacturer's product
To be read in conjunction with contract drawings and documents
Vendor/Manufacturer to provide sample for approval by the consultant before installation
Installation method as per manufacturer's specs.

PROJECT: RATAN TATA GALLERY

LEGEND REF:

TSL-3A

Project No.:

Area: Display Shelf

Date: 23rd March'24

Item: Megnetic track mounted Variable Beam Spotlight

Qty: (In Nos.)

15

Model No.: Generic

Description: Adjustable megnetic track-mounted variable beam spotlight for 24V/48V LED lamp with external dimmable power supply. Additional accessories must be possible, viz, antiglare louver, and color filters.



Colour: Black (Subject to approval)

Lamp: 6W LED 600lm within SCDM 3, 90+ CRI, 3000° K

Beam Angle: Variable Beam (10° to 36°)

Lamp Base: N/A

Total Wattage: 8W

Control Gear: External dimmable LED Driver with local dimmer minimum 0.9PF, THDi≤10% & Current ripple ≤20%

Protection (IP): 20

Accessories:

Dimensions: As per image

Notes:

This is a generic specification based on a manufacturer's product

To be read in conjunction with contract drawings and documents

Vendor/Manufacturer to provide sample for approval by the consultant before installation

Installation method as per manufacturer's specs.

PROJECT: RATAN TATA GALLERY

LEGEND REF:

TSL-4

Project No.:

Area: Display Shelf

Date: 23rd March'24

Item: Megnetic track mounted linear washer

Qty: (In Nos.) 10

Model No.: Generic

Description: Adjustable megnetic track-mounted 24V/48V linear washer with external dimmable power supply.



Colour Black (Subject to approval)

Lamp 12W LED 1100lm within SCDM 3, 90+ CRI, 3000° K

Beam Angle Medium Beam (30°)

Lamp Base N/A

Total Wattage 14W

Control Gear External dimmable LED Driver with local dimmer minimum 0.9PF, THDi≤10% & Current ripple ≤20%

Protection (IP) 20

Accessories

Dimensions: Length: 200mm

Notes:

This is a generic specification based on a manufacturer's product
To be read in conjunction with contract drawings and documents
Vendor/Manufacturer to provide sample for approval by the consultant before installation
Installation method as per manufacturer's specs.

PROJECT: RATAN TATA GALLERY

LEGEND REF:

TSL-5

Project No.:

Area: Display Shelf

Date: 23rd March'24

Item: Track mounted Framing Projector

Qty: (In Nos.) 30

Model No.: Generic

Description: Adjustable 3-circuit track-mounted framing projector with built-in on board dimmable power supply and adjustable focus with four shaping blades at 90 deg positions.

Colour Grey (Subject to approval)

Lamp 50W LED 4000lm within SCDM 3, 90+ CRI, Tunable White

Beam Angle Wide beam with variable focus with four framing

Lamp Base N/A

Total Wattage 66W

Control Gear Integral dimmable LED driver (on board) with minimum 0.9PF, THDi≤10% & Current ripple ≤20%

Protection (IP) 20

Accessories

Dimensions: N/A



Notes:

This is a generic specification based on a manufacturer's product

To be read in conjunction with contract drawings and documents

Vendor/Manufacturer to provide sample for approval by the consultant before installation

Installation method as per manufacturer's specs.

PROJECT: RATAN TATA GALLERY

LEGEND REF:

WSL-1

Project No.:

Area: Display Shelf

Date: 23rd March'24

Item: Ceiling Recessed Wall Washer

Qty: (In Nos.) 10

Model No.: Generic

Description: Wall mounted 0-cut off linear fixed wall washer, with black finish and specular dark-optic reflector, fixture with 10W LED

Colour Black (Subject to approval)

Lamp 10W LED 1100lm within SCDM 3, 90+ CRI, 3000° K

Beam Angle 0-cut off wall washer

Lamp Base N/A

Total Wattage 12W

Control Gear External dimmable LED Driver with local dimmer minimum 0.9PF, THDi≤10% & Current ripple ≤20%

Protection (IP) 20

Accessories

Dimensions: Arm Length: 450mm



Notes:

This is a generic specification based on a manufacturer's product

To be read in conjunction with contract drawings and documents

Vendor/Manufacturer to provide sample for approval by the consultant before installation

Installation method as per manufacturer's specs.