ANNEXURE - 3

PROJECT:	PORCELAIN GALLERY	LEGEND REF:	CST-1A
Project No.: Area: Date: Item: Model No.: Description:	Display Shelf 23rd March'24 3 Circuit Suspended Track 3-Circuit Suspended Track System 3-Circuit 16A rated track system suitable fo surface/suspended mounted in black finish, connection and fixing accessories as describ	or ceiling , with all	(In Mtr.) 80
Colour Lamp Beam Angle Lamp Base Total Wattage Control Gear Protection (IP) Accessories Dimensions:	Grey (Subject to approval) N/A N/A N/A N/A N/A 20 Width: 37mm; Height: 40mm; Length: As pe		
Notes:	This is a generic specification based on a m To be read in conjunction with contract draw Vendor/Manufacturer to provide sample for a Installation method as per manufacturer's sp	rings and documents approval by the consultant before ins	tallation

PROJECT:	PORCELAIN GALLERY	LEGEND REF:	CST-2
Project No.: Area: Date: Item: Model No.:	Display Shelf 23rd March'24 Megnetic Track Generic	2000mm Lenght Qty: (In Nos.) 1000mm Lenght Qty: (In Nos.)	44 127
Description: Colour Lamp Beam Angle Lamp Base Total Wattage Control Gear Protection (IP) Accessories	Surface mounted 24V/48V megnetic micro track system. in black finish, with all connection, onboard dimmable power supply and fixing accessories as described Black (Subject to approval) N/A N/A N/A N/A N/A 20	1	
Dimensions:	As per image		
Notes:	This is a generic specification based on a manufactur To be read in conjunction with contract drawings and Vendor/Manufacturer to provide sample for approval Installation method as per manufacturer's specs.	documents	

PROJECT:	PORCELAIN GALLERY	LEGEND REF:	CST-3
Project No.: Area: Date: Item: Model No.:	Display Shelf 23rd March'24 H Profile With 3 Circuit Track EUTRAC H-Profile With 3 Circuit Track	Qty: (In Mtr.)	33
Description:	Aluminium-Extruded H-Profile, with provision for insertion and fixing of 3-Ckt track, complete with all rigid threaded stud suspension + coupling accessories.		3
Colour	Grey (Subject to approval)	70	
Lamp	N/A N/A		
Beam Angle Lamp Base	N/A N/A	RE	55
Total Wattage	N/A	55	22
Control Gear	N/A	1	
Protection (IP) Accessories	20		
Dimensions:	Width: 36mm; Height: 70mm; Length: As per site		
Notes:	This is a generic specification based on a manufactu To be read in conjunction with contract drawings and Vendor/Manufacturer to provide sample for approval Installation method as per manufacturer's specs.	documents	

PROJECT:	PORCELAIN GALLERY	LEGEND REF:	TSL-1A
Project No.: Area: Date: Item: Model No.:	Display Shelf 23rd March'24 Adjustable track mounted projectors Generic	Qty: (In Nos.)	118
Description: Colour Lamp	Adjustable 3-circuit track-mounted variable beam spotlight for LED lamp with built-in on board dimmable power supply. Additional accessories must be possible, viz, antiglare louver, and color filters. Grey (Subject to approval) 20W LED 1800lm within SCDM 3, 90+ CRI, 3000° K		
Beam Angle	Variable Beam (10° to 45°)		
Lamp Base Total Wattage Control Gear	N/A 22W Integral dimmable LED driver (on board) with minimum 0.9PF, THDi≤10% & Current ripple ≤20%		
Protection (IP) Accessories Dimensions:	20 50mm cowl with hunycomb louver As per image		
Notes:	This is a generic specification based on a manufactu To be read in conjunction with contract drawings and Vendor/Manufacturer to provide sample for approval Installation method as per manufacturer's specs.	I documents	

PROJECT:	PORCELAIN GALLERY	LEGEND REF:	TSL-2A
Project No.: Area: Date: Item: Model No.:	Display Shelf 23rd March'24 Track mounted Framing Projector Generic	Qty: (In Nos.)	12
Description: Colour Lamp Beam Angle Lamp Base Total Wattage Control Gear Protection (IP) Accessories Dimensions:	Adjustable 3-circuit track-mounted framing projector with built-in on board dimmable power supply and adjustable focus with four shaping blades at 90 deg positions. Grey (Subject to approval) 20W LED 1800Im within SCDM 3, 90+ CRI, 3000° K Wide beam with variable focus with four framing N/A 22W Integral dimmable LED driver (on board) with minimum 0.9PF, THDi≤10% & Current ripple ≤20% 20 As per image		
Notes:	This is a generic specification based on a manufactur To be read in conjunction with contract drawings and Vendor/Manufacturer to provide sample for approval Installation method as per manufacturer's specs.	documents	

PROJECT:	PORCELAIN GALLERY	LEGEND REF:	TSL-3
Project No.: Area: Date: Item: Model No.:	Display Shelf 23rd March'24 Megnetic track mounted Variable Beam Spotlight Generic	Qty: (In Nos.)	175
Description: Colour Lamp Beam Angle Lamp Base Total Wattage Control Gear Protection (IP) Accessories Dimensions:	Adjustable megnetic track-mounted variable beam spotlight for 24V/48V LED lamp with external dimmable power supply. Additional accessories must be possible, viz, antiglare louver, and color filters. Black (Subject to approval) 3W LED 300Im within SCDM 3, 90+ CRI, 3000° K Variable Beam (10° to 36°) N/A 5W External dimmable LED Driver with local dimmer minimum 0.9PF, THDi≤10% & Current ripple ≤20% 20	THE PARTY OF THE P	
Notes:	This is a generic specification based on a manufactur To be read in conjunction with contract drawings and Vendor/Manufacturer to provide sample for approval Installation method as per manufacturer's specs.	l documents	

PROJECT:	PORCELAIN GALLERY	LEGEND REF:	TSL-3A
Project No.: Area: Date: Item: Model No.:	Display Shelf 23rd March'24 Megnetic track mounted Variable Beam Spotlight Generic	Qty: (In Nos.)	100
Description: Colour Lamp Beam Angle Lamp Base Total Wattage Control Gear	Adjustable megnetic track-mounted variable beam spotlight for 24V/48V LED lamp with external dimmable power supply. Additional accessories must be possible, viz, antiglare louver, and color filters. Black (Subject to approval) 6W LED 600Im within SCDM 3, 90+ CRI, 3000° K Variable Beam (10° to 36°) N/A 8W External dimmable LED Driver with local dimmer minimum 0.9PF, THDi≤10% & Current ripple ≤20%		
Protection (IP) Accessories	20		
Dimensions:	As per image		
Notes:	This is a generic specification based on a manufactu To be read in conjunction with contract drawings and Vendor/Manufacturer to provide sample for approval Installation method as per manufacturer's specs.	documents	

PROJECT:	PORCELAIN GALLERY	LEGEND REF:	TSL-4
Project No.: Area: Date: Item: Model No.:	Display Shelf 23rd March'24 Megnetic track mounted linear washer Generic	Qty: (In Nos.)	158
Description:	Adjustable megnetic track-mounted 24V/48V linear washer with external dimmable power supply.		
Colour Lamp	Black (Subject to approval) 12W LED 1100lm within SCDM 3, 90+ CRI, 3000° K	A REAL PROPERTY.	
Beam Angle Lamp Base Total Wattage Control Gear	Medium Beam (30°) N/A 14W External dimmable LED Driver with local dimmer minimum 0.9PF, THDi≤10% & Current ripple ≤20%		
Protection (IP) Accessories	20		
Dimensions:	Length: 200mm		
Notes:	This is a generic specification based on a manufactor To be read in conjunction with contract drawings and Vendor/Manufacturer to provide sample for approval Installation method as per manufacturer's specs.	d documents	

PROJECT:	PORCELAIN GALLERY	LEGEND REF:	CRL-1
Project No.: Area: Date: Item: Model No.:	Display Shelf 23rd March'24 Ceiling Recessed Veriable Spotlight Generic	Qty: (In Nos	s.) 6
Description: Colour Lamp	Ceiling recessed veriable round, 355° swivel and 45° tilt directional light, with deep recessed LED lamp and specular dark-optic reflector White (Subject to approval) 12W LED 1100Im within SCDM 3, 90+ CRI, 3000° K		
Beam Angle Lamp Base Total Wattage Control Gear	(10° x 45°) N/A 14W External dimmable LED Driver with local dimmer minimum 0.9PF, THDi≤10% & Current ripple ≤20%		
Protection (IP) Accessories Dimensions:	20 As per image		4
Notes:	This is a generic specification based on a manufactu To be read in conjunction with contract drawings and Vendor/Manufacturer to provide sample for approval Installation method as per manufacturer's specs.	documents	n

PORCELAIN GALLERY	LEGEND REF:	LCL-1
Display Area 23rd March'24 Linear Triangular Light Generic	Qty: (In mtr.) 3
Floor mounted, triangular linear LED profile made with Aluminium extruded housing and polycarbonate clear diffuser. Natural Grey Body 15W Per Mtr. LED array within SCDM 3, 90+ CR 3000° K Wide flood N/A 16W External dimmable LED Driver with local dimmer minimum 0.9PF, THDi≤10% & Current ripple ≤20%	1000	
interconnecting leads for end-to-end interconnections.	d	
This is a generic specification based on a manufact To be read in conjunction with contract drawings an	d documents	allation
	Display Area 23rd March'24 Linear Triangular Light Generic Floor mounted, triangular linear LED profile made with Aluminium extruded housing and polycarbonate clear diffuser. Natural Grey Body 15W Per Mtr. LED array within SCDM 3, 90+ CR 3000° K Wide flood N/A 16W External dimmable LED Driver with local dimmer minimum 0.9PF, THDi≤10% & Current ripple ≤20% 20 Fitting accessories mounting bracket for display and interconnecting leads for end-to-end interconnecting leads for end-to-end interconnections. Width: 20 mm; Height: 20 mm; Length: As per site This is a generic specification based on a manufact To be read in conjunction with contract drawings an Vendor/Manufacturer to provide sample for approva	Display Area 23rd March'24 Linear Triangular Light Generic Floor mounted, triangular linear LED profile made with Aluminium extruded housing and polycarbonate clear diffuser. Natural Grey Body 15W Per Mtr. LED array within SCDM 3, 90+ CRI, 3000° K Wide flood N/A 16W External dimmable LED Driver with local dimmer minimum 0.9PF, THDis10% & Current ripple ≤20% 20 Fitting accessories mounting bracket for display and interconnecting leads for end-to-end interconnections. Width: 20 mm; Height: 20 mm; Length: As per site This is a generic specification based on a manufacturer's product To be read in conjunction with contract drawings and documents Vendor/Manufacturer to provide sample for approval by the consultant before insta

PROJECT:	PORCELAIN GALLERY	LEGEND REF:	PL-1
Project No.: Area: Date: Item: Model No.:	Staircase 23rd March'24 Pendant Light Generic	Qty: (In Nos.)	1
Description: Colour Lamp Beam Angle Lamp Base Total Wattage Control Gear Protection (IP) Accessories Dimensions:	Ceiling suspended decorative pendat light Black 12W LED within SCDM 3, 80+ CRI, 3000° K Wide flood N/A 13W External non-dimmable LED Driver minimum 0.9PF, THDi≤10% & Current ripple ≤20% 20 Fitting accessories for ceiling suspension Dia: 400 mm; Height: 450 mm		
Notes:	This is a generic specification based on a manufactu To be read in conjunction with contract drawings and Vendor/Manufacturer to provide sample for approval Installation method as per manufacturer's specs.	documents	