

**PROJECT: BUDDHIST GALLERY**

**LEGEND REF:**

**TSL-1**

**Project No.:**

**Area:** Display Area

**Date:** 06th Jun'23

**Item:** Adjustable track mounted projectors

Qty: (In Nos.) 23

**Model No.:** Generic

**Description:** Adjustable 3-circuit track-mounted variable beam spotlight for LED lamp with built-in on board dimmable power supply. Additional accessories must be possible, viz, antiglare louver, and color filters.

**Colour** Black (Subject to approval)

**Lamp** 20W LED 1800lm within SCDM 3, 90+ CRI, 3000° K

**Beam Angle** Variable Beam (10° to 45°)

**Lamp Base** N/A

**Total Wattage** 13W

**Control Gear** Integral dimmable LED driver (on board) with minimum 0.9PF, THDi≤10% & Current ripple ≤20%

**Protection (IP)** 20

**Accessories**

**Dimensions:** As per image

**Vendor Details:** Sun Glow Green Solution / Forma / iGuzzini or approved vendor

**Source:**

**Telephone:**

**Address:**

**Fax:**

**Contact:**

**Email:**

**Notes:**

This is a generic specification based on a manufacturer's product  
To be read in conjunction with contract drawings and documents  
Vendor/Manufacturer to provide sample for approval by the consultant before installation  
Installation method as per manufacturer's specs.



**PROJECT: BUDDHIST GALLERY**

**LEGEND REF:**

**TSL-2**

**Project No.:**

**Area:** Display Area

**Date:** 06th Jun'23

**Item:** Track mounted Framing Projector

Qty: (In Nos.) 1

**Model No.:** Generic

**Description:** Adjustable 3-circuit track-mounted framing projector with built-in on board dimmable power supply and adjustable focus with four shaping blades at 90 deg positions.

**Colour:** Black (Subject to approval)

**Lamp:** 11W LED 850lm within SCDM 3, 90+ CRI, 3000° K

**Beam Angle:** Wide beam with variable focus with four framing blades

**Lamp Base:** N/A

**Total Wattage:** 13W

**Control Gear:** Integral dimmable LED driver (DALI) with minimum 0.9PF, THDi≤10% & Current ripple ≤20%

**Protection (IP):** 20

**Accessories:**

**Dimensions:** As per image

**Vendor Details:** Sun Glow Green Solution / Forma / iGuzzini or approved vendor

**Source:**

**Telephone:**

**Address:**

**Fax:**

**Contact:**

**Email:**

**Notes:**

This is a generic specification based on a manufacturer's product  
To be read in conjunction with contract drawings and documents  
Vendor/Manufacturer to provide sample for approval by the consultant before installation  
Installation method as per manufacturer's specs.



**PROJECT: BUDDHIST GALLERY**

**LEGEND REF:**

**CST-2**

**Project No.:**

**Area:** Display Area

**Date:** 06th Jun'23

**Model No.:** Megnetic Track  
Generic

Qty: (In Mtr.) 9

**Description:** Surface mounted megnetic micro track system. in black finish, with all connection and fixing accessories as described

**Colour:** Black (Subject to approval)

**Lamp:** N/A

**Beam Angle:** N/A

**Lamp Base:** N/A

**Total Wattage:** N/A

**Control Gear:** N/A

**Protection (IP):** 20

**Accessories**

**Dimensions:** As per image

**Vendor Details:** Artlite / Forma / iGuzzini or approved vendor

**Source:**

**Telephone:**

**Address:**

**Fax:**

**Contact:**

**Email:**

**Notes:**

This is a generic specification based on a manufacturer's product  
To be read in conjunction with contract drawings and documents  
Vendor/Manufacturer to provide sample for approval by the consultant before installation  
Installation method as per manufacturer's specs.



**PROJECT: BUDDHIST GALLERY**

**LEGEND REF:**

**TSL-3**

**Project No.:**

**Area:** Display Area

**Date:** 06th Jun'23

**Item:** Megnetic track mounted Variable Beam Spotlight

Qty: (In Nos.) 20

**Model No.:** Generic

**Description:** Adjustable megnetic track-mounted variable beam spotlight for LED lamp with external dimmable power supply. Additional accessories must be possible, viz, antiglare louver, and color filters.

**Colour:** Black (Subject to approval)

**Lamp:** 5W LED 900lm within SCDM 3, 90+ CRI, 3000° K

**Beam Angle:** Variable Beam (10° to 30°)

**Lamp Base:** N/A

**Total Wattage:** 6W

**Control Gear:** External dimmable LED Driver with minimum 0.9PF, THDi≤10% & Current ripple ≤20%

**Protection (IP):** 20

**Accessories:**

**Dimensions:** As per image

**Vendor Details:** Flos / Forma / XAL Lighting / iGuzzini or approved vendor

**Source:**

**Telephone:**

**Address:**

**Fax:**

**Contact:**

**Email:**

**Notes:**

This is a generic specification based on a manufacturer's product  
To be read in conjunction with contract drawings and documents  
Vendor/Manufacturer to provide sample for approval by the consultant before installation  
Installation method as per manufacturer's specs.



**PROJECT: BUDDHIST GALLERY**

**LEGEND REF:**

**FSL-1**

**Project No.:**

**Area:** Display Area

**Date:** 06th Jun'23

**Model No.:** Window Sill Light  
Generic

Qty: (In Nos.) 2

**Description:** Floor mounted LED window sill light with a deep recessed luminaire, Fixture needs to be supplied with surface mounting accessories.

**Colour:** Dark Grey (Subject to approval)

**Lamp:** 3W LED array within SCDM 3, 80+ CRI, 3000° K

**Beam Angle:** Linear wash

**Lamp Base:** N/A

**Total Wattage:** 5W

**Control Gear:** Integral dimmable LED driver with minimum 0.9PF, THDi≤10% & Current ripple ≤20%

**Protection (IP):** 65

**Accessories:** Fitting accessories for floor

**Dimensions:** As per image

**Vendor Details:** iGuzzini / M3 Lighting / K-Lite or approved equivalent

**Source:**

**Telephone:**

**Address:**

**Fax:**

**Contact:**

**Email:**

**Notes:**

This is a generic specification based on a manufacturer's product  
To be read in conjunction with contract drawings and documents  
Vendor/Manufacturer to provide sample for approval by the consultant before installation  
Installation method as per manufacturer's specs.



**PROJECT: BUDDHIST GALLERY**

**LEGEND REF:**

**LCL-1**

**Project No.:**

**Area:** Display Area

**Date:** 06th Jun'23

**Model No.:** Linear Asymmetric LED Strip

Qty: (In Mtr.) 9

Generic (Recessed Asymmetric Wash 7W LED)

**Description:** Wall/wood recessed, asymmetric linear LED flood made with Aluminium extruded housing with frosted PAMMA diffuser

**Colour:** Black and frosted diffuser

**Lamp:** 7W per mtr. LED array within SCDM 3, 90+ CRI, 3000° K

**Beam Angle:** Diffuse

**Lamp Base:** LV connector

**Total Wattage:** 10W per mtr.

**Control Gear:** External dimmable LED Driver with minimum 0.9PF, THDi≤10% & Current ripple ≤20%

**Protection (IP):** 20

**Accessories:** Fitting accessories for wood

**Dimensions:** As per image

**Vendor Details:** M3 Lighting / ALS Lighting / Sun Glow Solutions or approved equivalent

**Source:**

**Telephone:**

**Address:**

**Fax:**

**Contact:**

**Email:**


**Notes:**

This is a generic specification based on a manufacturer's product

To be read in conjunction with contract drawings and documents.

Vendor/Manufacturer to provide sample for approval by the consultant before installation

Installation method as per manufacturer's specs.



**PROJECT: BUDDHIST GALLERY**

**LEGEND REF:**

**LCL-2**

**Project No.:**

**Area:** Display Area

**Date:** 06th Jun'23

**Item:** Linear Triangular Light For Display

Qty: (In Mtr.) 2

**Model No.:** Generic

**Description:** Display mounted, triangular linear LED profile made with Aluminium extruded housing and polycarbonate frosted diffuser.

**Colour** Natural Grey Body

**Lamp** 15W Per Mtr. LED array within SCDM 3, 90+ CRI, 3000° K

**Beam Angle** Diffuse

**Lamp Base** N/A

**Total Wattage** 16W

**Control Gear** External dimmable LED Driver with minimum 0.9PF, THDi $\leq$ 10% & Current ripple  $\leq$ 20%

**Protection (IP)** 20

**Accessories** Fitting accessories mounting bracket for display and interconnecting leads for end-to-end interconnections.

**Dimensions:** Width: 20 mm; Height: 20 mm; Length: As per site

**Vendor Details:** Flos / Forma / XAL Lighting / Luxia or approved vendor

**Source:**

**Telephone:**

**Address:**

**Fax:**

**Contact:**

**Email:**

**Notes:**

This is a generic specification based on a manufacturer's product  
To be read in conjunction with contract drawings and documents  
Vendor/Manufacturer to provide sample for approval by the consultant before installation  
Installation method as per manufacturer's specs.

