

LDP

LUMINAIRE TENDER PACKAGE

LIGHTING DESIGN PARTNERSHIP PTY LTD  
213-217 PALMER STREET  
DARLINGHURST  
NSW 2010  
AUSTRALIA

# CSMVS Ancient Worlds

Mumbai, India

**The following information is required for review:**

1. Filled tender form as supplied in excel format
2. Complete Datasheet
3. IES files

**SS01**

|                      |  |                   |                      |
|----------------------|--|-------------------|----------------------|
| <b>Luminaire Ref</b> |  |                   |                      |
| Description          | Spotlight compatible with GLOBAL track, with provision for attachment of anti-glare louvre and colour filter |                   |                      |
| <b>Housing</b>       |  | <b>Electrical</b> | <b>LED</b>           |
| Mounting             | Track mounted  | Power Supply      | Technology           |
|                      |  | INTEGRAL          |                      |
| Dimensions           | Dia: 70mm max<br>H: 160mm max  | Distance          | Colour Temp Group    |
|                      |  |                   |                      |
| <b>Appearance</b>    |  | Control           | CRI minimum          |
| Colour               | White  | DALI              | 90                   |
| Finish               |  |                   |                      |
| Special Requirements |  | Wattage maximum   | Beam Distribution    |
|                      |  | 15W               |                      |
| <b>Details</b>       |  |                   | Lumen Output minimum |
|                      |  |                   | 1200lm               |
|                      |  |                   | Notes                |
|                      |  |                   |                      |

Recommended  
Manufacturers

Specification

[LDP\_T\_921\_v3\_01]

**SS02**

|                      |  |                   |                      |
|----------------------|--|-------------------|----------------------|
| <b>Luminaire Ref</b> |  |                   |                      |
| Description          | Spotlight compatible with GLOBAL track, with provision for attachment of anti-glare louvre and colour filter |                   |                      |
| <b>Housing</b>       |  | <b>Electrical</b> | <b>LED</b>           |
| Mounting             | Track mounted  | Power Supply      | Technology           |
|                      |  | INTEGRAL          |                      |
| Dimensions           | Dia: 70mm max<br>H: 160mm max  | Distance          | Colour Temp Group    |
|                      |  |                   |                      |
| <b>Appearance</b>    |  | Control           | CRI minimum          |
| Colour               | White  | DALI              | 90                   |
| Finish               |  |                   |                      |
| Special Requirements |  | Wattage maximum   | Beam Distribution    |
|                      |  | 15W               |                      |
| <b>Details</b>       |  |                   | Lumen Output minimum |
|                      |  |                   | 1200lm               |
|                      |  |                   | Notes                |
|                      |  |                   |                      |

Recommended  
Manufacturers

Specification

[LDP\_T\_921\_v3\_01]

**SS03**

|                      |  |                              |                                 |
|----------------------|--|------------------------------|---------------------------------|
| <b>Luminaire Ref</b> |  |                              |                                 |
| Description          | Spotlight compatible with GLOBAL track, with provision for attachment of anti-glare louvre and colour filter |                              |                                 |
| <b>Housing</b>       |  | <b>Electrical</b>            | <b>LED</b>                      |
| Mounting             | Track mounted  | Power Supply<br><br>INTEGRAL | Technology<br><br>A LED         |
| Dimensions           | Dia: 70mm max<br>H: 160mm max  | Distance                     | Colour Temp Group<br><br>5000 K |
| <b>Appearance</b>    |  | Control                      | CRI minimum                     |
| Colour               | Black  | DALI                         | 90                              |
| Finish               |  | Wattage maximum              | Beam Distribution<br><br>Narrow |
| Special Requirements |  | 15W                          | Lumen Output minimum<br>1200lm  |
| <b>Details</b>       |  | Notes                        |                                 |
|                      |  |                              |                                 |

Recommended  
Manufacturers

Specification

[LDP\_T\_921\_v3\_01]

**SS06**

|                      |  |                              |                                 |
|----------------------|--|------------------------------|---------------------------------|
| <b>Luminaire Ref</b> |  |                              |                                 |
| Description          | Spotlight compatible with GLOBAL track, with provision for attachment of anti-glare louvre and colour filter |                              |                                 |
| <b>Housing</b>       |  | <b>Electrical</b>            | <b>LED</b>                      |
| Mounting             | Surface mounted  | Power Supply<br><br>INTEGRAL | Technology<br><br>A LED         |
| Dimensions           | Dia: 70mm max<br>H: 160mm max  | Distance                     | Colour Temp Group<br><br>5000 K |
| <b>Appearance</b>    |  | Control                      | CRI minimum                     |
| Colour               | White  | DALI                         | 90                              |
| Finish               |  | Wattage maximum              | Beam Distribution<br><br>Medium |
| Special Requirements |  | 15W                          | Lumen Output minimum<br>1200lm  |
| <b>Details</b>       |  | Notes                        |                                 |
|                      |  |                              |                                 |

Recommended  
Manufacturers

Specification

[LDP\_T\_921\_v3\_01]

**SS07**

|                      |  |                      |                   |
|----------------------|--|----------------------|-------------------|
| <b>Luminaire Ref</b> |  |                      |                   |
| Description          | Spotlight compatible with GLOBAL track, with provision for attachment of anti-glare louvre and colour filter |                      |                   |
| <b>Housing</b>       |  | <b>Electrical</b>    | <b>LED</b>        |
| Mounting             | Surface mounted  | Power Supply         | Technology        |
|                      |  | INTEGRAL             |                   |
| Dimensions           | Dia: 70mm max<br>H: 160mm max  | Distance             | Colour Temp Group |
|                      |  |                      |                   |
| <b>Appearance</b>    |  | Control              | CRI minimum       |
| Colour               | White  | DALI                 | 90                |
| Finish               |  | Wattage maximum      | Beam Distribution |
| Special Requirements |  | 15W                  |                   |
| <b>Details</b>       |  | Lumen Output minimum | Notes             |
|                      |  | 1200lm               |                   |
|                      |  |                      |                   |

Recommended  
Manufacturers

Specification

[LDP\_T\_921\_v3\_01]

**SS12**

|                      |  |                      |                   |
|----------------------|--|----------------------|-------------------|
| <b>Luminaire Ref</b> |  |                      |                   |
| Description          | Spotlight with internal framer with zoom lens(14° - 24°), compatible with GLOBAL track, with provision for attachment of colour filter |                      |                   |
| <b>Housing</b>       |  | <b>Electrical</b>    | <b>LED</b>        |
| Mounting             | Track mounted  | Power Supply         | Technology        |
|                      |  | INTEGRAL             |                   |
| Dimensions           | Dia: 80mm max<br>H: 250mm max  | Distance             | Colour Temp Group |
|                      |  |                      |                   |
| <b>Appearance</b>    |  | Control              | CRI minimum       |
| Colour               | White  | DALI                 | 90                |
| Finish               |  | Wattage maximum      | Beam Distribution |
| Special Requirements |  | 30W                  |                   |
| <b>Details</b>       |  | Lumen Output minimum | Notes             |
|                      |  | 1500lm               |                   |
|                      |  |                      |                   |

Recommended  
Manufacturers

Specification

[LDP\_T\_921\_v3\_01]

**SS13**

| Luminaire Ref        |                               | Description  |          | Icons             |  |
|----------------------|-------------------------------|--|----------|-------------------|--|
|                      |                               | Spotlight with internal framer with fixed lens (45°), compatible with GLOBAL track, with provision for attachment of colour filter |          |                   |  |
| Housing              |                               | Electrical   |          | LED               |  |
| Mounting             | Track mounted                 | Power Supply   | INTEGRAL |                   |  |
| Dimensions           | Dia: 80mm max<br>H: 250mm max | Distance   |          |                   |  |
| Appearance           |                               | Control  |          | CRI minimum       |  |
| Colour               | White                         | DALI   |          | 90                |  |
| Finish               |                               | Wattage maximum  |          | Beam Distribution |  |
| Special Requirements |                               | 30W  |          |                   |  |
| Details              |                               | Lumen Output minimum   |          | Notes             |  |
|                      |                               | 1500lm   |          |                   |  |

Recommended  
Manufacturers

Specification

[LDP\_T\_921\_v3\_01]

**SS14**

| Luminaire Ref        |                               | Description  |          | Icons             |  |
|----------------------|-------------------------------|--|----------|-------------------|--|
|                      |                               | Spotlight with internal framer with zoom lens(20° - 30°), compatible with GLOBAL track, with provision for attachment of colour filter |          |                   |  |
| Housing              |                               | Electrical   |          | LED               |  |
| Mounting             | Track mounted                 | Power Supply   | INTEGRAL |                   |  |
| Dimensions           | Dia: 80mm max<br>H: 250mm max | Distance   |          |                   |  |
| Appearance           |                               | Control  |          | CRI minimum       |  |
| Colour               | White                         | DALI   |          | 90                |  |
| Finish               |                               | Wattage maximum  |          | Beam Distribution |  |
| Special Requirements |                               | 30W  |          |                   |  |
| Details              |                               | Lumen Output minimum   |          | Notes             |  |
|                      |                               | 1500lm   |          |                   |  |

Recommended  
Manufacturers

Specification

[LDP\_T\_921\_v3\_01]