



KEY PLAN

LEGEND

SYMBOL	DESCRIPTION
	ADJUSTABLE LIGHT
	FOCUS LIGHT
	DOWNLIGHTER
	TRACK
	12W LED CEILING RECESSED/ SURFACE LIGHT FITTING
	WALL MOUNTED LIGHT FITTING
	LED BOX TYPE LIGHT FITTING
	6A, ONE WAY SWITCH
	16A, DP SWITCH WITH INDICATOR LAMP
	6/16A, SOCKETS CEILING MOUNTED.
	16A, SOCKETS OUTLET WITH SWITCH
	20A, MODULAR SOCKET WITH ON / OFF PB SWITCH.
	SMOKE DETECTOR
	DATA OUTLET.
	DISTRIBUTION BOARD.
	OCCUPANCY SWITCH.
	CCTV

APPROVAL	TENDER	EXECUTION	AS BUILT	SIGNATURE

DRAWING STATUS			
REV	DESCRIPTION		
B	2024/03/14	REVISED AS PER ARCH. CHANGES	
A	2023/12/20	REVISED AS PER LATEST ARCH DRG.	
rev	date	description	chk.

consultants
 122-123, SH COMMERCIAL CENTRE, GOVANDI STATION ROAD, DECONA, MUMBAI - 400 088. TEL 2850011
 project CSMVS MAIN BUILDING RENOVATION & UPGRADATION

clients CSMVS, mumbai.

title MUMBAI GALLERY LAYOUT - ELECTRICAL (KARL & MEHERBAI)

north	drawn	MANUJ Y. WAREKAR	drawing no.	revision
	scale	1:1:50	2406-KMKG-11	B
	date	2023/03/08		
	checked			

- NOTES :-
- 1) ALL WIRING IN MS CONDUITS.
 - 2) ALL LIGHTS ARE CONTROLLED DIRECTLY FROM SWITCHES UNLESS SWITCHES ARE SHOWN OTHERWISE.
 - 3) WIRING DETAILS :-
 - * LIGHTING/6A SOCKETS - 3 x 1.5 sqmm Cu. FRLS
 - * 16A SOCKETS - 3 x 2.5 sqmm Cu. FRLS
 - * FIRE ALARM - 2C-1.5 sqmm SHIELDED CABLES.
 - 4) ALL 6/16A, OR CLUSTER (TWIN) TO BE WIRED FROM PDB
 - 5) ALL TRACK LIGHTS TO BE WIRED USING 3 x 2.5 sqmm FRLS WIRES IN CONDUIT
 - 6) ALL NIGHT LIGHTS (NL1 TO 3) ARE TO BE USING 3 x 1.5 sqmm COPPER WIRES IN CONDUIT.

DRG. PATHS