





Ref	Description	Rate Per Unit	Quantity	Unit	Amount	GST %	Lead time (weeks)
<b>BR01</b>	LED Rigid Linear with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Surface mounted, complete with all fixing accessories. Diffuse output. . Dali Dimmable. For electrical parameters refer General Notes.						
	Wattage (W/m)	Max	10				
	Lumens ( lm/m)	Min	750				
	IP	Min	24				
	CCT		3000				
	CRI	Min	90				
	Beam		Diffuse				
	Colour		Black				
	Length To suit installation						
	Width (mm)	Max	75				
	Height (mm)	Max	100				
	Manufacturer Offered						
	Model Offered						
				10.3	m	0.00	
<b>BR02</b>	LED Linear strip with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Recessed, complete with all fixing accessories. Wide (30 - 40 degree) beam. . Dali Dimmable. For electrical parameters refer General Notes.						
	Wattage (W/m)	Max	10				
	Lumens ( lm/m)	Min	750				
	IP	Min	24				
	CCT		3000				
	CRI	Min	90				
	Beam		Wide				
	Colour		Black				
	Length To suit installation						
	Width (mm)	Max	25				
	Height (mm)	Max	15				
	Manufacturer Offered						
	Model Offered						
				2.4	m	0.00	





Ref	Description	Rate Per Unit	Quantity	Unit	Amount	GST %	Lead time (weeks)	
<b>BR03</b>	LED Recessed Linear Display Lighting with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Recessed, complete with all fixing accessories. Wide (30 - 40 degree) beam. . 300mm wide modules. For electrical parameters refer General Notes.							
	Wattage (W)		Max	8		0		
	Lumens (lm)		Min	2000		0		
	IP		Min	24		0		
	CCT			3000		0		
	CRI		Min	95		0		
	Beam			Wide		0		
	Colour			Black		0		
						0		
	Length (mm)		Max	300		0		
	Width (mm)			15		0		
	Recess Depth (mm)		Max	25		0		
	Manufacturer Offered							
	Model Offered							
			178	ea	0.00			
<b>BR04</b>	LED Recessed Display Spotlights with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Recessed, complete with all fixing accessories. Medium (12 - 25 degree) beam. . For electrical parameters refer General Notes.							
	Wattage (W)		Max	2		0		
	Lumens (lm)		Min	600		0		
	IP		Min	24		0		
	CCT			4000		0		
	CRI		Min	90		0		
	Beam			Medium		0		
	Colour			TBD		0		
	Dia (mm)		Max	40		0		
	Plate dia (mm)		Max	39		0		
	Length (mm)		Max	14		0		
	Recess Depth (mm)		Max	15		0		
	Manufacturer Offered							
	Model Offered							
			258	ea	0.00			



Ref	Description	Rate Per Unit	Quantity	Unit	Amount	GST %	Lead time (weeks)							
<b>BR05</b>	LED Linear Flexible Strip Diffused. with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Recessed, complete with all fixing accessories. Wide (30 - 40 degree) beam. Skirting light for thematic display poles. 650mm length of BR05 strip required per pole. Total length required (0.65 * 15) is 9.75m. Dali Dimmable. For electrical parameters refer General Notes.													
	Wattage (W)							Max	10	0				
	Lumens (lm)							Min	750	0				
	IP							Min	24	0				
	CCT								3000	0				
	CRI							Min	90	0				
	Beam								Wide	0				
	Colour								N/A	0				
										0				
	Length To suit installation									0				
	Width (mm)							Max	20	0				
	Height (mm)							Max	20	0				
	Manufacturer Offered													
	Model Offered													
			15	ea	0.00									
<b>BS01</b>	LED High Output Linear Gantry Luminaire with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Surface mounted, complete with all fixing accessories. Wide (30 - 40 degree) beam. Single Gantry light. . 600mm wide modules. For electrical parameters refer General Notes.													
	Wattage (W)							Max	7	0				
	Lumens (lm)							Min	1660	0				
	IP							Min	24	0				
	CCT								3000	0				
	CRI							Min	95	0				
	Beam								Wide	0				
	Colour								TBD	0				
	Dia (mm)							Max	13.5	0				
	Length (mm)							Max	600	0				
	Height (mm)								220	0				
	Manufacturer Offered													
	Model Offered													
										10	ea	0.00		



# Tender Return Form



Coin Gallery CSMVS, Mumbai



LDP\_2491\_Tender Return Form\_issued on\_2019-12-04

Ref	Description	Rate Per Unit	Quantity	Unit	Amount	GST %	Lead time (weeks)				
<b>BS02</b>	LED Freestanding Display spotlights with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Surface mounted, complete with all fixing accessories. Medium (12 - 25 degree) beam. . For electrical parameters refer General Notes.										
	Wattage (W)							Max	6	0	
	Lumens (lm)							Min	600	0	
	IP							Min	24	0	
	CCT								3000	0	
	CRI							Min	90	0	
	Beam								Medium	0	
	Colour								TBD	0	
	Dia (mm)							Max	25	0	
	Tube dia (mm)							Max	10	0	
	Height (mm)							Max	500	0	
	Manufacturer Offered										
	Model Offered										
<b>CR01</b>	LED Diffused Spotlights (Set of 8) with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Recessed, complete with all fixing accessories. Medium (12 - 25 degree) beam. . For electrical parameters refer General Notes.										
	Wattage (W)							Max	2	0	
	Lumens (lm)							Min	300	0	
	IP							Min	24	0	
	CCT								3000	0	
	CRI							Min	90	0	
	Beam								Medium	0	
	Colour								Black	0	
										0	
	Length To suit installation									0	
	Width (mm)							Max	200	0	
	Height (mm)							Max	15	0	
	Manufacturer Offered										
	Model Offered										
					28	ea	0.00				



Ref	Description	Rate Per Unit	Quantity	Unit	Amount	GST %	Lead time (weeks)				
<b>DR01</b>	LED Round fixed downlight with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Recessed, complete with all fixing accessories. Medium (12 - 25 degree) beam. . Dali Dimmable. For electrical parameters refer General Notes.										
	Wattage (W)							Max	13		0
	Lumens (lm)							Min	950		0
	IP							Min	24		0
	CCT								3000		0
	CRI							Min	90		0
	Beam								Medium		0
	Colour								Black		0
	Dia (mm)							Max	85		0
	Recess Depth (mm)							Max	120		0
											0
	Manufacturer Offered										
	Model Offered										
			11	ea	0.00						
<b>DR02</b>	LED Recessed Adjustable Narrow Beam. with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Recessed, complete with all fixing accessories. Narrow (8 - 10 degree) beam. . Dali Dimmable. For electrical parameters refer General Notes.										
	Wattage (W)							Max	13		0
	Lumens (lm)							Min	950		0
	IP							Min	24		0
	CCT								3000		0
	CRI							Min	90		0
	Beam								Narrow		0
	Colour								Black		0
	Dia (mm)							Max	85		0
	Recess Depth (mm)							Max	120		0
											0
	Manufacturer Offered										
	Model Offered										
										4	ea

Ref	Description	Rate Per Unit	Quantity	Unit	Amount	GST %	Lead time (weeks)				
<b>DR03</b>	LED Recessed Adjustable Downlight Medium Beam. with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Recessed, complete with all fixing accessories. Medium (12 - 25 degree) beam. . Dali Dimmable. For electrical parameters refer General Notes.										
	Wattage (W)							Max	13	0	
	Lumens (lm)							Min	950	0	
	IP							Min	24	0	
	CCT								3000	0	
	CRI							Min	90	0	
	Beam								Medium	0	
	Colour								Black	0	
	Dia (mm)							Max	85	0	
	Recess Depth (mm)							Max	120	0	
										0	
	Manufacturer Offered										
	Model Offered										
										3	ea
<b>DR04</b>	LED Recessed Fixed Downlight Medium Beam with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Recessed, complete with all fixing accessories. Medium (12 - 25 degree) beam. . Dali Dimmable. For electrical parameters refer General Notes.										
	Wattage (W)							Max	13	0	
	Lumens (lm)							Min	950	0	
	IP							Min	24	0	
	CCT								4000	0	
	CRI							Min	90	0	
	Beam								Medium	0	
	Colour								Black	0	
	Dia (mm)							Max	85	0	
	Recess Depth (mm)							Max	120	0	
										0	
	Manufacturer Offered										
	Model Offered										
										19	ea

Ref	Description	Rate Per Unit	Quantity	Unit	Amount	GST %	Lead time (weeks)			
<b>DR05</b>	LED Downlight with Honeycomb Louvre. with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Recessed, complete with all fixing accessories. Medium (12 - 25 degree) beam. . Dali Dimmable. For electrical parameters refer General Notes.									
	Wattage (W)	Max						20	0	
	Lumens (lm)	Min						1700	0	
	IP	Min						24	0	
	CCT							4000	0	
	CRI	Min						90	0	
	Beam							Medium	0	
	Colour							Black	0	
	Dia (mm)	Max						100	0	
	Recess Depth (mm)	Max						120	0	
									0	
	Manufacturer Offered									
	Model Offered									
			9	ea	0.00					
<b>DS01</b>	LED Surface Mounted Spotlight Narrow Beam. with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Surface mounted, complete with all fixing accessories. Wide (30 - 40 degree) beam. . Dali Dimmable. For electrical parameters refer General Notes.									
	Wattage (W)	Max						9	0	
	Lumens (lm)	Min						700	0	
	IP	Min						24	0	
	CCT							3000	0	
	CRI	Min						90	0	
	Beam							Wide	0	
	Colour							Black	0	
	Dia (mm)	Max						70	0	
	Length (mm)	Max						81	0	
	Height (mm)	Max						130	0	
									0	
	Manufacturer Offered									
	Model Offered									
			15	ea	0.00					

Ref	Description	Rate Per Unit	Quantity	Unit	Amount	GST %	Lead time (weeks)	
<b>DS02</b>	LED Surface Mounted Spotlight Medium Beam. with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Surface mounted, complete with all fixing accessories. Medium (12 - 25 degree) beam. . Dali Dimmable. For electrical parameters refer General Notes.							
	Wattage (W)		Max	9		0		
	Lumens (lm)		Min	700		0		
	IP		Min	24		0		
	CCT			3000		0		
	CRI		Min	90		0		
	Beam			Medium		0		
	Colour			Black		0		
	Dia (mm)		Max	70		0		
	Length (mm)		Max	81		0		
	Height (mm)			130		0		
	Manufacturer Offered							
	Model Offered							
			29	ea	0.00			
<b>DS03</b>	LED Surface Mounted Spotlight Medium. with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Surface mounted, complete with all fixing accessories. Medium (12 - 25 degree) beam. . Dali Dimmable. For electrical parameters refer General Notes.							
	Wattage (W)		Max	9		0		
	Lumens (lm)		Min	800		0		
	IP		Min	24		0		
	CCT			4000		0		
	CRI		Min	90		0		
	Beam			Medium		0		
	Colour			Black		0		
	Dia (mm)		Max	70		0		
	Length (mm)		Max	81		0		
	Height (mm)			130		0		
	Manufacturer Offered							
	Model Offered							
			15	ea	0.00			



Ref	Description	Rate Per Unit	Quantity	Unit	Amount	GST %	Lead time (weeks)	
<b>DS04</b>	LED Surface Mounted Spotlight with Optical Framer with Remote Dimmable Dimming using DALI or equal Addressable protocol transformer. Suitable for Indoor use. Surface mounted, complete with all fixing accessories. Wide (30 - 40 degree) beam. Beam angle 55 degrees for Philips Signify PerfectBeam v2 luminaire.. Dali Dimmable. For electrical parameters refer General Notes.							
	Wattage (W)		Max	25		0		
	Lumens (lm)		Min	1560		0		
	IP		Min	24		0		
	CCT			3000		0		
	CRI		Min	90		0		
	Beam			Wide		0		
	Colour			Black		0		
	Length (mm)		Max	225		0		
	Width (mm)		Max	180		0		
	Height (mm)		Max	260		0		
	Manufacturer Offered							
	Model Offered							
					4	ea	0.00	
<b>SS01</b>	LED Image Projector with Integral Non-Dimmable transformer. Suitable for Indoor use. Surface mounted, complete with all fixing accessories. Wide (30 - 40 degree) beam. . For electrical parameters refer General Notes.							
	Wattage (W)		Max	10		0		
	Lumens (lm)		Min	1230		0		
	IP		Min	24		0		
	CCT			3000		0		
	CRI		Min	N/A		0		
	Beam			Wide		0		
	Colour			Black		0		
	Length (mm)		Max	200		0		
	Width (mm)		Max	150		0		
	Height (mm)		Max	150		0		
	Manufacturer Offered							
	Model Offered							
					6	ea	0.00	